

## Seat Belt for Forklift

Seat Belt for Forklift - Explained in the Regulation guidelines are the application of operative restraints and seatbelts on forklifts. It says that the responsibility falls on the employers' to be able to make sure that every machinery, piece of equipment and tool is used properly used in accordance to the directions of the manufacturer.

In regards to their use, design, maintenance, inspection and fabrication Rough Terrain forklifts need to satisfy the regulations of ANSI Standard ASME B56.6-1992.

Side boom tractors and mobile machine along with a Rollover Protective Structure, or ROPS for short, should have seat belts that meet the requirements of the Society of Automotive Engineers, or SAE, Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whichever mobile machinery includes seat belts required by law, the driver and subsequent passengers need to ensure they use the belts each time the vehicle is in motion or engaged in operation since this can cause the machine to become unstable and therefore, not safe.

If a seat belt or other driver restraint is required on a lift truck.

While working a lift truck, the seat belt requirements will depend on a number of factors. Contributing factors to this determination might include whether or not the the forklift is outfitted with a Rollover Protective Structure, the kind of lift truck itself and the year the forklift was made. The manufacturer's directions and the requirements of the applicable standard are referenced in the Regulation.

With regards to to a driver restraint device, enclosure or system, ANSI Standard ASME B56.1-1993 with regards to powered industrial trucks, is intended to help the driver in lessening the danger of entrapment of the head and/or torso between the truck and the ground in the event of a tip over. The system or restraint device could comprise a seat belt, even if a seat belt is not essentially a part of such machine or system.